



**Bruce® / Hartco®**

# FLOORING PRODUCTS

---

BROUGHT TO YOU BY:

**TAYLOR™**  
WITH YOU EVERY STEP™



## BEHIND THE BRAND

Bruce® Flooring has been synonymous with premium, quality hardwood flooring since its founding by E.L. Bruce in 1884. The Bruce brand is one of a select few flooring companies that has almost universal name recognition with contactors and consumers alike. Now owned by AHF, the Bruce brand will continue its legacy of manufacturing and supplying premier products to the flooring industry.



## BRUCE<sup>®</sup> and TAYLOR

In 2020, AHF and TAYLOR formed a partnership to uphold the tradition of the Bruce brand adhesive and floor care products and to further support and enhance the level of service offered. At Taylor, we are proud to be the exclusive manufacturer and distributor for the Bruce lines of hardwood and resilient adhesives as well as the sole provider for the Bruce brand of floor cleaning products.



## BRUCE® WOOD FLOORING ADHESIVES

Easily identified by the famous Bruce-red lid and eye-catching design, this adhesive line lives up to the reputation of the Bruce name. Designed for maximum performance with Bruce hardwood flooring, these adhesives can also be used with most hardwood flooring installations.

# BRUCE® WOOD FLOORING ADHESIVES

## SUMMIT™ SELECT

Unlimited Moisture Vapor Barrier  
Hard-Set Elastomeric Adhesive



- Unlimited moisture protection
- 100% RH, no moisture or pH testing
- Permanent, waterproof bond
- Wet-set installation
- 45-minute working time
- Shelf life = 1 year

## PROCONNECT™ PLUS

90% Moisture Vapor Barrier Hard-  
Set Elastomeric Adhesive



- 90% moisture protection
- 90% RH, 10 lbs MVER, 14 pH
- Permanent, waterproof bond
- Wet-set installation
- 45-60-minute working time
- Shelf life = 1 year

## EQUALIZER™ PRO

Moisture-Cured Urethane Wood  
Flooring Adhesive



- Moderate moisture tolerance
- 75% RH, 5 lbs MVER, 9 pH
- High-strength, waterproof bond
- Wet-set installation
- 45-60-minute working time
- Shelf life = 1 year

## EVERSEAL™

Floating Floor Tongue & Groove  
Adhesive



- N/A
- N/A
- High-strength, water-resistant bond
- Wet-set installation
- 30-60-minute working time
- Shelf life = 1 year

## GLUE ASSIST PRO

Wood Flooring Glue Assist  
Adhesive



- N/A
- N/A
- Aggressive, waterproof bond
- Wet-set installation
- 45-minute working time
- Shelf life = 1 year

RECOMMENDED FOR ALL OTHER AHF BRANDS:

**Hartco, Robbins, LM, Capella, tmbr, HomerWood**

# SUMMIT™ SELECT

Unlimited Moisture Vapor Barrier Hard-Set Elastomeric Adhesive



Recommended  
for use with:

**Bruce**®

Capella

**Hartco**

H/W  
HOMERWOOD®

**LM**  
Flooring®

**ROBBINS**

**tubr.**



RH



\*NTR (100%)

pH



\*NTR (14)

MVER



\*NTR

OPEN  
TIME



0 min

WORKING  
TIME



45 min

CURE  
TIME



12 hrs

LIGHT  
TRAFFIC



6 hrs

HEAVY  
TRAFFIC



6 hrs

IIC



\*\*68 dB

STC



\*\*62 dB

\*NTR = No Testing Required

\*\*Ratings based on 6" concrete slab with a suspended wallboard ceiling overlaid with 3/8" engineered hardwood flooring

# SUMMIT™ SELECT

Unlimited Moisture Vapor Barrier Hard-Set Elastomeric Adhesive



Recommended  
for use with:

**Bruce**  
Capella

**Hartco**  
H|W  
HOMERWOOD™

**LM**  
Flooring®

**ROBBINS**

**tubr.**

## WHY USE

- Unlimited moisture protection (porous slab)
- Cost savings potential
- No moisture or pH testing required
- Permanent, waterproof bond
- Isocyanate-free
- Non-staining and easy to clean
- 1-step installation
- Elastomeric membrane
- Faster construction timeline
- Sound control (IIC, STC)
- Can be used over cutback residue (see TDS)
- Protects flooring from alkali attack
- Anti-microbial technology

RH



\*NTR (100%)

pH



\*NTR (14)

MVER



\*NTR

OPEN  
TIME



0 min

WORKING  
TIME



45 min

CURE  
TIME



12 hrs

LIGHT  
TRAFFIC



6 hrs

HEAVY  
TRAFFIC



6 hrs

IIC



\*\*68 dB

STC



\*\*62 dB

\*NTR = No Testing Required

\*\*Ratings based on 6" concrete slab with a suspended wallboard ceiling overlaid with 3/8" engineered hardwood flooring

# SUMMIT™ SELECT

Unlimited Moisture Vapor Barrier Hard-Set Elastomeric Adhesive



Recommended  
for use with:

**Bruce**  
Capella

**Hartco**  
H|W  
HOMERWOOD™

**LM**  
Flooring®

**ROBBINS**

**tubr.**

## COST SAVINGS POTENTIAL

**SKIP  
TESTING**

**SAVE \$0.15/sf**

- By not having to perform any moisture or pH testing
  - 3 tests in the first 1000 ft<sup>2</sup>
  - 1 test every 1000 ft<sup>2</sup> after initial (ex. 10,000ft<sup>2</sup> = 12 tests)

**START  
INSTALLING**

**SAVE DAYS or WEEKS**

- By not having costly construction delays
  - Moisture testing takes 1 – 3 days
  - If testing fails it can delay a jobsite by weeks

**SAVE \$4-5/sf**

By not having to perform traditional moisture mitigation steps  
1.) bead-blast 2.) patch & level 3.) prime 4.) 2-part epoxy 5.) prime

savings are based on an estimated national average and may vary by location and jobsite

RH



\*NTR (100%)

pH



\*NTR (14)

MVER



\*NTR

OPEN  
TIME



0 min

WORKING  
TIME



45 min

CURE  
TIME



12 hrs

LIGHT  
TRAFFIC



6 hrs

HEAVY  
TRAFFIC



6 hrs

IIC



\*\*68 dB

STC



\*\*62 dB

\*NTR = No Testing Required

\*\*Ratings based on 6" concrete slab with a suspended wallboard ceiling overlaid with 3/8" engineered hardwood flooring

# SUMMIT™ SELECT

Unlimited Moisture Vapor Barrier Hard-Set Elastomeric Adhesive



Recommended  
for use with:

**Bruce**®

Capella

**Hartco**®

H|W  
HOMERWOOD™

LM  
Flooring®

ROBBINS®

 tmbr.

## APPROVED FLOORING TYPES

- Acrylic Impregnated Plank
- Bamboo Flooring
- Cork Flooring
- Cork-Backed Hard Surface
- Cork Underlayment
- Hardwood (engineered)
- Hardwood (parquet)
- Hardwood (solid)



Coverage: 20-70 sf/gal

RH



\*NTR (100%)

pH



\*NTR (14)

MVER



\*NTR

OPEN  
TIME



0 min

WORKING  
TIME



45 min

CURE  
TIME



12 hrs

LIGHT  
TRAFFIC



6 hrs

HEAVY  
TRAFFIC



6 hrs

IIC



\*\*68 dB

STC



\*\*62 dB

\*NTR = No Testing Required

\*\*Ratings based on 6" concrete slab with a suspended wallboard ceiling overlaid with 3/8" engineered hardwood flooring

# PROCONNECT™ PLUS

90% Moisture Vapor Barrier Hard-Set Elastomeric Adhesive



Recommended  
for use with:

**Bruce**

Capella

**Hartco**

H/W  
HOMERWOOD™

**LM**  
Flooring®

**ROBBINS**

 **tmbr.**



RH



90%

pH



\*NTR (14)

MVER



10 lbs

OPEN  
TIME



0 min

WORKING  
TIME



45 min

CURE  
TIME



12 hrs

LIGHT  
TRAFFIC



6 hrs

HEAVY  
TRAFFIC



6 hrs

\*NTR = No Testing Required

# PROCONNECT™ PLUS

90% Moisture Vapor Barrier Hard-Set Elastomeric Adhesive



Recommended  
for use with:

**Bruce**  
Capella

**Hartco**  
H|W  
HOMERWOOD™

**LM**  
Flooring®

**ROBBINS**

**tibr.**

## WHY USE

- 90% moisture protection (porous slab)
- Attractive price point
- Permanent, waterproof bond
- Isocyanate-free
- Non-staining and easy to clean
- 1-part installation
- Elastomeric bond
- Sound control
- Can be used over cutback residue (see TDS)
- Protects flooring from alkali attack
- Anti-microbial technology

RH



90%

pH



\*NTR (14)

MVER



10 lbs

OPEN  
TIME



0 min

WORKING  
TIME



45 min

CURE  
TIME



12 hrs

LIGHT  
TRAFFIC



6 hrs

HEAVY  
TRAFFIC



6 hrs

\*NTR = No Testing Required

# PROCONNECT™ PLUS

90% Moisture Vapor Barrier Hard-Set Elastomeric Adhesive



Recommended  
for use with:

**Bruce**  
Capella

**Hartco**  
H|W  
HOMERWOOD™

**LM**  
Flooring®

**ROBBINS**

**tubr.**

## APPROVED FLOORING TYPES

- Acrylic Impregnated Plank
- Bamboo Flooring
- Cork Flooring
- Cork-Backed Hard Surface
- Cork Underlayment
- Hardwood (engineered)
- Hardwood (parquet)
- Hardwood (solid)

 Coverage: 20-70 sf/gal



RH



90%

pH



\*NTR (14)

MVER



10 lbs

OPEN  
TIME



0 min

WORKING  
TIME



45 min

CURE  
TIME



12 hrs

LIGHT  
TRAFFIC



6 hrs

HEAVY  
TRAFFIC



6 hrs

\*NTR = No Testing Required

# EQUALIZER™ PRO

Moisture-Cured Urethane Wood Flooring Adhesive



Recommended  
for use with:

**Bruce**

Capella

**Hartco**

H/W  
HOMERWOOD™

**LM**  
Flooring®

**ROBBINS**

 **tmbr.**



RH



75%

pH



5-9

MVER



\*5 lbs

OPEN  
TIME



10 min

WORKING  
TIME



45-60 min

CURE  
TIME



24 hrs

LIGHT  
TRAFFIC



4 hrs

HEAVY  
TRAFFIC



12 hrs

\*This product does not provide moisture protection

# EQUALIZER™ PRO

Moisture-Cured Urethane Wood Flooring Adhesive



Recommended  
for use with:

**Bruce**

Capella

**Hartco**

H|W  
HOMERWOOD™

LM  
Flooring®

ROBBINS

tibr.

## BENEFITS

- Strong, elastomeric bond
- Fast grab
- Non-slumping formula
- Easy installation
- Low VOC, low odor

## APPROVED FLOORING TYPES

- Hardwood (engineered, parquet, solid)
- Recycled rubber
- Cork flooring
- Bamboo (not strand woven)



Coverage: 50-70 sf/gal

RH



75%

pH



5-9

MVER



\*5 lbs

OPEN  
TIME



10 min

WORKING  
TIME



45-60 min

CURE  
TIME



24 hrs

LIGHT  
TRAFFIC



4 hrs

HEAVY  
TRAFFIC



12 hrs

\*This product does not provide moisture protection

# EVERSEAL™

Floating Floor Tongue & Groove Adhesive



Recommended  
for use with:

**Bruce**  
Capella

**Hartco**  
H|W  
HOMERWOOD™

**LM**  
Flooring®

**ROBBINS**

**tubr.**



OPEN  
TIME



0 min

WORKING  
TIME



5-10 min

LIGHT  
TRAFFIC



12 hrs

HEAVY  
TRAFFIC



24 hrs

# EVERSEAL™

Floating Floor Tongue & Groove Adhesive



Recommended  
for use with:

**Bruce®**  
Capella

**Hartco®**

H|W  
HOMERWOOD®

**LM**  
Flooring®

**ROBBINS®**

**tibr.**

## BENEFITS

- Strong, water-resistant bond
- Resists moisture and mold
- Easy installation
- Low VOC, low odor
- ANSI Type II compliant
- Easy clean-up, non-etching

## APPROVED FLOORING TYPES

- Engineered flooring
- Laminate flooring

Coverage: 400 lf/16oz bottle

OPEN  
TIME



0 min

WORKING  
TIME



5-10 min

LIGHT  
TRAFFIC



12 hrs

HEAVY  
TRAFFIC



24 hrs

# GLUE ASSIST PRO

Floating Floor Tongue & Groove Adhesive



Recommended  
for use with:

**Bruce**  
Capella

**Hartco**  
H|W  
HOMERWOOD

**LM**  
Flooring

**ROBBINS**

**tمبر.**

## BENEFITS

- Reduces friction squeaks common with nail/staple-down installations
- Wet-set, early grab, fast-curing formula
- High-strength, elastomeric bond
- Non-staining and easy to clean
- LEED v4 contributing (CDPH v1.2)

## APPROVED FLOORING TYPES

- Engineered and solid hardwood
- Bamboo
- Dry-back parquet
- Cork flooring
- Cork underlayment
- Cork-backed hard surface
- Acrylic impregnated plank

OPEN  
TIME



0 min

WORKING  
TIME



45 min

CURE  
TIME



12 hrs



## BRUCE® RESILIENT FLOORING ADHESIVES

Quickly distinguished by their bold, blue lids, this state-of-the-art line of resilient adhesives will tackle even the most challenging installation environments. Engineered to perform from residential to heavy-commercial applications, these easy-to-use, one-part products will keep your flooring installations secure.

# BRUCE® RESILIENT FLOORING ADHESIVES

FOR COMMERCIAL USE

## APEX PRO™

Unlimited Moisture Vapor Barrier  
Hard-Set Resilient Adhesive



- Unlimited moisture protection
- 100% RH, no moisture or pH testing
- Permanent, waterproof bond
- Wet-set installation
- 45-minute working time
- Shelf life = 1 year

FOR COMMERCIAL USE

## BondLink™

Hard-Set Transitional Pressure  
Sensitive Resilient Adhesive



- High moisture tolerance
- 99% RH, 12 lbs MVER, 12 pH
- Permanent, waterproof bond
- Dry/semi-wet installation
- 3-hour working time
- Shelf life = 2 years

FOR RESIDENTIAL USE

## TuffLink™

Firm-Set Pressure Sensitive  
Resilient & Carpet Adhesive



- High moisture tolerance
- 99% RH, 12 lbs MVER, 12 pH
- High-strength, waterproof bond
- Dry/semi-wet installation
- 12-hour working time
- Shelf life = 2 years

RECOMMENDED FOR ALL OTHER AHF CONTRACT BRANDS:

**Hartco Contract, Robbins Contract, LM Contract**

RECOMMENDED FOR ALL RESIDENTIAL AHF BRANDS:

**Hartco, Robbins, LM Flooring**

# APEX PRO™

Unlimited Moisture Vapor Barrier Hard-Set Elastomeric Adhesive

FOR COMMERCIAL USE



Recommended  
for use with:

**Bruce**  
CONTRACT

**Hartco**  
CONTRACT

**LM**  
Flooring®

CONTRACT

ROBBINS  
CONTRACT



RH



\*NTR (100%)

pH



\*NTR (14)

MVER



\*NTR

OPEN  
TIME



0 min

WORKING  
TIME



45 min

CURE  
TIME



6 hrs

LIGHT  
TRAFFIC



3 hrs

HEAVY  
TRAFFIC



4 hrs

ROLLING  
LOADS



8 hrs

ΔIIC



\*\*18 dB

\*NTR = No Testing Required

\*\*ΔIIC rating based on 6" concrete slab overlaid with 3.2mm LVP flooring

# APEX PRO™

Unlimited Moisture Vapor Barrier Hard-Set Elastomeric Adhesive

FOR COMMERCIAL USE



Recommended  
for use with:

**Bruce**  
CONTRACT

**Hartco**  
CONTRACT

**LM**  
Flooring®

CONTRACT

**ROBBINS**  
CONTRACT

RH



\*NTR (100%)

pH



\*NTR (14)

MVER



\*NTR

OPEN  
TIME



0 min

WORKING  
TIME



45 min

CURE  
TIME



6 hrs

LIGHT  
TRAFFIC



3 hrs

HEAVY  
TRAFFIC



4 hrs

ROLLING  
LOADS



8 hrs

ΔIIC



\*\*18 dB

## WHY USE

- Unlimited moisture protection (porous slab)
- Cost savings potential
- No moisture or pH testing required
- No sub-slab moisture barrier required
- Topical liquid resistance (water, spills, etc.)
- Permanent, waterproof bond
- 1-step installation
- Self-leveling, elastomeric membrane
- Excellent plasticizer migration resistance
- Faster construction timeline
- 6-hour cure (heat weld, wet mop, strip/finish)
- Rapid occupancy times
- Extreme heavy rolling loads
- Installs multiple flooring types
- Sound control (IIC, STC)
- Anti-microbial technology

\*NTR = No Testing Required

\*\*ΔIIC rating based on 6" concrete slab overlaid with 3.2mm LVP flooring

# APEX PRO™

Unlimited Moisture Vapor Barrier Hard-Set Elastomeric Adhesive

FOR COMMERCIAL USE



Recommended for use with:

**Bruce**  
CONTRACT

**Hartco**  
CONTRACT

**UM**  
Flooring®

CONTRACT

**ROBBINS**  
CONTRACT

## COST SAVINGS POTENTIAL

**SKIP TESTING**

**SAVE \$0.15/sf**

- By not having to perform any moisture or pH testing
- 3 tests in the first 1000 ft<sup>2</sup>
- 1 test every 1000 ft<sup>2</sup> after initial (ex. 10,000ft<sup>2</sup> = 12 tests)

**START INSTALLING**

**SAVE DAYS or WEEKS**

- By not having costly construction delays
- Moisture testing takes 1 – 3 days
- If testing fails it can delay a jobsite by weeks

**SAVE \$4-5/sf**

By not having to perform traditional moisture mitigation steps  
1.) bead-blast 2.) patch & level 3.) prime 4.) 2-part epoxy 5.) prime

savings are based on an estimated national average and may vary by location and jobsite

RH



\*NTR (100%)

pH



\*NTR (14)

MVER



\*NTR

OPEN TIME



0 min

WORKING TIME



45 min

CURE TIME



6 hrs

LIGHT TRAFFIC



3 hrs

HEAVY TRAFFIC



4 hrs

ROLLING LOADS



8 hrs

ΔIIC



\*\*18 dB

\*NTR = No Testing Required

\*\*ΔIIC rating based on 6" concrete slab overlaid with 3.2mm LVP flooring

# APEX PRO™

Unlimited Moisture Vapor Barrier Hard-Set Elastomeric Adhesive

FOR COMMERCIAL USE



Recommended  
for use with:

**Bruce**  
CONTRACT

**Hartco**  
CONTRACT

**UM**  
Flooring®

CONTRACT

**ROBBINS**  
CONTRACT

## APPROVED FLOORING TYPES

- Cork Flooring
- Cork-Backed Hard Surface
- Cork Underlayment
- Linoleum
- LVT/LVP
- Rigid Core (SPC, WPC, WSC, ETC.)
- Rubber (tile/sheet)
- Sheet (felt-backed)
- Sheet (fiberglass)
- Sheet (heterogeneous)
- Sheet (homogeneous)
- Stair Treads (rubber, vinyl)
- VCT/VET



Coverage: 150-260 sf/gal

RH



\*NTR (100%)

pH



\*NTR (14)

MVER



\*NTR

OPEN  
TIME



0 min

WORKING  
TIME



45 min

CURE  
TIME



6 hrs

LIGHT  
TRAFFIC



3 hrs

HEAVY  
TRAFFIC



4 hrs

ROLLING  
LOADS



8 hrs

ΔIIC



\*\*18 dB

\*NTR = No Testing Required  
\*\*ΔIIC rating based on 6" concrete slab overlaid with 3.2mm LVP flooring

# BondLink™

Hard-Set Transitional Pressure Sensitive Resilient Flooring Adhesive

FOR COMMERCIAL USE



Recommended  
for use with:

**Bruce**  
CONTRACT

**Hartco**  
CONTRACT

**LM**  
Flooring®

CONTRACT

ROBBINS  
CONTRACT



RH



99%

pH



5-12

MVER



12 lbs

DRY  
TIME



\*30-60 min

WORKING  
TIME



\*3 hrs

CURE  
TIME



12 hrs

LIGHT  
TRAFFIC



\*0 min

HEAVY  
TRAFFIC



24 hrs

ROLLING  
LOADS



48 hrs

\*Data reference PSA application only. See technical data sheet for complete details.

# BondLink™

Hard-Set Transitional Pressure Sensitive Resilient Flooring Adhesive

FOR COMMERCIAL USE



Recommended  
for use with:

**Bruce**  
CONTRACT

**Hartco**  
CONTRACT

**UM**  
Flooring®

CONTRACT

ROBBINS  
CONTRACT

## WHY USE

- High moisture tolerance
- Permanent, waterproof bond
- Ideal for heavy rolling loads
- Immediate access to light traffic
- Installs multiple flooring types
- Elastomeric bond
- Excellent plasticizer migration resistance
- Anti-microbial technology

RH



99%

pH



5-12

MVER



12 lbs

DRY  
TIME



\*30-60 min

WORKING  
TIME



\*3 hrs

CURE  
TIME



12 hrs

LIGHT  
TRAFFIC



\*0 min

HEAVY  
TRAFFIC



24 hrs

ROLLING  
LOADS



48 hrs

\*Data reference PSA application only. See technical data sheet for complete details.

# BondLink™

Hard-Set Transitional Pressure Sensitive Resilient Flooring Adhesive

FOR COMMERCIAL USE



Recommended  
for use with:

**Bruce**  
CONTRACT

**Hartco**  
CONTRACT

**LM**  
Flooring®

CONTRACT

**ROBBINS**  
CONTRACT

## APPROVED FLOORING TYPES

- Cork-Backed Hard Surface
- Cork Underlayment
- LVT/LVP
- Rigid Core (SPC, WPC, WSC, ETC.)
- Rubber (tile and sheet)
- Sheet (fiberglass)
- Sheet (heterogeneous)
- Sheet (homogeneous)
- Stair Treads (rubber, vinyl)
- VCT/VET



Coverage: 150-350 sf/gal



RH



99%

pH



5-12

MVER



12 lbs

DRY  
TIME



\*30-60 min

WORKING  
TIME



\*3 hrs

CURE  
TIME



12 hrs

LIGHT  
TRAFFIC



\*0 min

HEAVY  
TRAFFIC



24 hrs

ROLLING  
LOADS



48 hrs

\*Data reference PSA application only. See technical data sheet for complete details.

# TuffLink™

Firm-Set Pressure Sensitive Resilient & Carpet Flooring Adhesive

FOR RESIDENTIAL USE



Recommended  
for use with:

**Bruce**  
Capella  
**Hartco**  
**LM**  
Flooring®  
**ROBBINS**



RH



99%

pH



5-12

MVER



12 lbs

DRY  
TIME



\*30-60 min

WORKING  
TIME



\*12 hrs

CURE  
TIME



12 hrs

LIGHT  
TRAFFIC



\*0 min

HEAVY  
TRAFFIC



24 hrs

ROLLING  
LOADS



48 hrs

\*Data reference PSA application only. See technical data sheet for complete details.

# TuffLink™

Firm-Set Pressure Sensitive Resilient & Carpet Flooring Adhesive

FOR RESIDENTIAL USE



Recommended  
for use with:

**Bruce**  
Capella  
**Hartco**  
LM  
Flooring®  
ROBBINS

## WHY USE

- High moisture tolerance
- High-strength, waterproof bond
- Repositionable installation
- Immediate access to light traffic
- Attractive price point
- Installs multiple flooring types
- 12 hours of working time
- ColorReady™ technology
- Simple installation
- Elastomeric bond
- Plasticizer migration resistance
- Anti-microbial technology

RH



99%

pH



5-12

MVER



12 lbs

DRY  
TIME



\*30-60 min

WORKING  
TIME



\*12 hrs

CURE  
TIME



12 hrs

LIGHT  
TRAFFIC



\*0 min

HEAVY  
TRAFFIC



24 hrs

ROLLING  
LOADS



48 hrs

\*Data reference PSA application only. See technical data sheet for complete details.

# TuffLink™

Firm-Set Pressure Sensitive Resilient & Carpet Flooring Adhesive

FOR RESIDENTIAL USE



Recommended  
for use with:

**Bruce**  
Capella  
**Hartco**  
LM  
Flooring®  
ROBBINS

## APPROVED FLOORING TYPES

- Breathable Broadloom Carpet
- Carpet (6 ft vinyl-backed)
- Carpet (Action Bac, hot-melt & Jute back)
- Carpet (double-stick carpet to cushion)
- Carpet (double-stick cushion to substrate)
- Carpet (HP vinyl-backed broadloom)
- Carpet (polyurethane, rubber-backed)
- Carpet (unitary & unitary Action Bac)
- Carpet (woven-backed)
- Carpet Tile (hard- & soft-backed)
- Cork-Backed Hard Surface
- Cork Underlayment
- LVT/LVP
- Rigid Core (SPC, WPC, WSC, ETC.)
- Rubber (tile/sheet)
- Sheet (fiberglass)
- Sheet (heterogeneous)
- Sheet (homogeneous)
- Stair Treads (rubber, vinyl)
- VCT/VET

 Coverage: 90-350 sf/gal 

RH



99%

pH



5-12

MVER



12 lbs

DRY  
TIME



\*30-60 min

WORKING  
TIME



\*12 hrs

CURE  
TIME



12 hrs

LIGHT  
TRAFFIC



\*0 min

HEAVY  
TRAFFIC



24 hrs

ROLLING  
LOADS



48 hrs

\*Data reference PSA application only. See technical data sheet for complete details.



## BRUCE<sup>®</sup> FLOOR CLEANING PRODUCTS

Your hardwood flooring's secret to a long, beautiful life is the family of Bruce cleaning products. Designed and formulated to care for Bruce flooring, these products are provided by Taylor Adhesives.

# BRUCE® FLOOR CLEANING PRODUCTS

## HARDWOOD & LAMINATE FLOOR CLEANER

For: non-waxed hardwood and laminate



- Residue free
- Fast drying
- Safely cleans
- Spray bottle = 32 fluid oz
- Refill bottle = 64 fluid oz
- Shelf life = 2 years

## MULTI-PURPOSE FLOOR CLEANER

For: tile, vinyl, stone, ceramic



- Residue free
- Streak free
- Safely cleans
- Spray bottle = 32 fluid oz
- Refill bottle = 64 fluid oz
- Shelf life = 2 years

## FRESH FINISH FLOOR POLISH

Urethane Top-Coat



- Revitalize dull, worn and scratched floors
- Durable, long-lasting finish
- Easy to use, quick drying
- 32 fluid oz squeeze bottle
- Shelf life = 2 years

## HARDWOOD & LAMINATE CLEANING SYSTEM

Microfiber Mop Cover Kit



- Contains all needed tools for easy cleaning
  - Swivel head mop w/telescoping pole
  - Reversible, replaceable mop cover
  - 32 oz hardwood & laminate spray-bottle
- Easy use - spray & wipe
- Use with – non-waxed hardwood & laminate
- Shelf life = 2 years



**Bruce® / Hartco®**

# FLOORING PRODUCTS

BROUGHT TO YOU BY:

**TAYLOR™**  
WITH YOU EVERY STEP™