







**SAHARA**® UNLIMITED MOISTURE VAPOR BARRIER

- No costly moisture testing required
- 1-part system increases ease of install
- pH blocker protects from alkali attack

- Fast, 8-hour cure time improves efficiency
- LEED v4 contributing (VOC 0.05 g/L)





|  |  |   |  |
|--|--|---|--|
| <b>RH</b><br><br>100% | <b>pH</b><br><br>5-14 | <b>MVER</b><br><br>N/A | <b>Cure Time</b><br><br>8 hrs |
|--|--|---|--|



**ZEPHYR**® 95% MOISTURE VAPOR BARRIER, ENCAPSULATOR & DETACKIFIER

- 1-part, roller-applied system cures within 1-2 hours
- Encapsulates old adhesive residue (including cutback)

- pH blocker protects from alkali attack
- Primes porous substrates (including gypcrete)
- LEED v4 contributing (VOC 0 g/L)

|  |  |   |  |
|--|--|---|--|
| <b>*RH</b><br><br>95% | <b>pH</b><br><br>5-14 | <b>*MVER</b><br><br>15 lbs | <b>Cure Time</b><br><br>1-2 hrs |
|--|--|---|--|





\*Data icons reference 2-coat application only.



**ENHANCE**® SURFACE BOND PROMOTER & ENCAPSULATOR

- Cures to a textured, highly bondable surface
- Encapsulates old adhesive residue (including cutback)

- pH blocker protects from alkali attack
- Seals porous substrates (including gypcrete)
- LEED v4 contributing (VOC 0.05 g/L)







|   |  |   |  |
|---|--|---|--|
| <b>RH</b><br><br>90% | <b>pH</b><br><br>5-14 | <b>MVER</b><br><br>8 lbs | <b>Cure Time</b><br><br>1-2 hrs |
|---|--|---|--|



**SOUNDLEVEL**® LIQUID ACOUSTICAL UNDERLAYMENT

- Self-leveling technology reduces telegraphing
- 1-part system increases ease of install

- Fast, 1-2 hour cure time improves efficiency
- Seals substrate and isolates cracks up to 1/8"
- LEED v4 contributing (VOC 0.1 g/L)

|   |  |  |  |   |   |
|---|--|--|--|---|---|
| <b>RH</b><br><br>90% | <b>pH</b><br><br>5-14 | <b>MVER</b><br><br>10 lbs | <b>Cure Time</b><br><br>1-2 hrs | <b>*IIC</b><br><br>69 dB | <b>*STC</b><br><br>66 dB |
|---|--|--|--|---|---|




\*Data icons apply to a specific assembly.



**FINALE**® COVE BASE ADHESIVE

- Cures white, non-staining and easy to clean
- Aggressive tack, fast-grab formula

- High-strength, water-resistant bond
- Strong plasticizer migration resistance
- LEED v4 contributing (VOC 8 g/L)

|  |  |   |
|--|--|---|
| <b>Open Time</b><br><br>0 min | <b>Working Time</b><br><br>30 min | <b>Cure Time</b><br><br>12 hrs |
|--|--|---|