

TIMBERLINE

PRODUCT HIGHLIGHT

ESSENTIALS LINE

WOOD FLOORING ADHESIVE

Moisture-Cured Urethane Wood Flooring Adhesive

Timberline Wood Flooring Adhesive is a low V.O.C., one component, moisture curing polyurethane adhesive. Designed for easy trowel-on application over concrete or wood substrates to install materials such as solid (shorts) and engineered wood flooring, parquet flooring, recycled rubber flooring, cork flooring and bamboo flooring (not strand woven).



WHY USE TIMBERLINE?

- Attractive price point
- Low odor
- Strong, elastomeric bond
- Fast grab
- Non-slump
- 1-part installation
- Low VOC

APPROVED FLOORING TYPES

- Hardwood (solid, engineered, parquet)
- Recycled rubber
- Cork flooring
- Bamboo (not strand woven)



RH
75%*



PH
5-9



MVER
5 lbs*



OPEN
TIME
10 MIN



WORKING
TIME
45-60 MIN



CURE
TIME
24 HRS



LIGHT
TRAFFIC
4 HRS



HEAVY
TRAFFIC
12 HRS

Coverage: 35-180 sf/gal

NOTE: See technical data sheet for details.

*This product does not provide moisture protection.

Shelf Life: 1 Year

AVAILABLE IN 3.5-GALLON PAIL

