



DESCRIPTION: Taylor 2062 Premium Seam Sealer For Fiberglass Sheet Goods

Taylor 2062 Premium Seam Sealer is a solvent free sealer designed for seaming fiberglass sheet goods in direct glue down installations.

INSTRUCTIONS

1. Prepare flooring and seam according to manufacturer's instructions.
2. Apply a bead of 2062 Seam Sealer to the foamed edges of the fiberglass sheets to be seamed.
3. Join the sheet edges by butting them together while the seam sealer is still wet.
4. Wipe off any excess seam sealer with a damp cloth.
5. Dried sealer can be removed with Taylor Touchdown #9 Adhesive Remover/Stripper. Avoid soaking the flooring with solvent. Do not pour solvent directly onto flooring.
6. Protect the seam area for a minimum of 6 hours to allow the seam sealer to dry.

PHYSICAL PROPERTIES

- Base: Latex polymer blend
Appearance: Off-white liquid
Open Time: Up to 1 hour depending on the porosity of the subfloor.
Shelf Life: One year in unopened container at 70° F.
Coverage: 225 linear feet per 8oz.
Flammability: Non-flammable. Complies with NFPA Class A and UBC Class 1 as determined by ASTM E84 and also passes the Pill Test.
Features: Solvent-free, non-flammable, freeze/thaw stable to 10° F (-12° C). Made with anti-microbial agents that will provide its dry film with protection from fungal growth. This protection is determined using the ASTM G21 test method.
Clean Up: Use soap and water while wet. Use Taylor Touchdown #9 Adhesive Remover/Stripper when dry.

CAUTION

DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.

WARRANTY INFORMATION

This product is manufactured according to exacting quality control standards and is warranted to be free from manufacturing defects. Defective material called to our attention within one year of manufacture will be replaced. No guarantee, expressed or implied, is made regarding the performance of this product since the manner and conditions of application are beyond our control. For complete warranty information, call Technical Services at 800-868-4583; visit us on the web at www.wftaylor.com; or e-mail us at info@wftaylor.com.