

DESCRIPTION: TOUCHDOWN® 700 TACK STRIP CONTACT ADHESIVE

Specially formulated for bonding carpet tack strip to almost any flooring surface-concrete, marble, terrazzo or wood. High strength formula permits immediate stretching. High rubber content provides more contact area and less soaking into porous flooring surfaces.

APPLICATION

Coat both bonding surfaces. Let dry about 20 minutes. Place tackless in exact position desired. Taylor 700 bonds instantly on contact and cannot be repositioned. Complete bond by pounding the strip with a hammer.

PHYSICAL PROPERTIES

Base: Chlorinated Rubber, Resin Blend
Appearance: Natural, thick syrup
Odor: Aromatic solvent odor
Open Time: Thin coat: approximately 10 – 20 minutes
Bead: approximately 40 minutes
Coverage: Approximately 1,000 linear feet of tackless per gallon.
Shelf Life: One year in unopened container at 70°F
Flammability: EXTREMELY FLAMMABLE
Clean up: Clean up spills immediately and discard accordingly. Remove dried adhesive with W. F. Taylor #9 Adhesive remover/Stripper.

CAUTION

DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.

LIMITED WARRANTY

This product is manufactured according to exacting quality control standards and is warranted to be free from manufacturing defects. Defective material called to our attention within one year of manufacture will be replaced. No guarantee, expressed or implied, is made regarding the performance of this product since the manner and conditions of application are beyond our control. For information, call Technical Services at 800-868-4583; visit us on the web at www.wftaylor.com; or e-mail us at info@wftaylor.com.

W.F. TAYLOR CO., INC. * FONTANA, CA 800.397.4583 * DALTON, GA 800.868.4583