

Touchdown 722

Water Based Pad Adhesive

DESCRIPTION

Taylor Touchdown 722 is a specially formulated latex-based adhesive for bonding all types of carpet padding to all types of floors. It exhibits a fast-wet suction and will hold pad in place so that the carpet can be stretched immediately. It is easy to pour and ready to use.

INSTRUCTIONS

The surface to which Taylor 722 is to be applied must be clean and dry, and free of excessive alkali. Remove all foreign substances such as wax, grease, dirt and sand. Using spout, apply beads of adhesive about 1/4" wide, 3" to 4" away from each wall and in a criss-cross pattern the full length of all pad seams. Using a scrap of pad or carpet, spread the adhesive to form an even film, permit the adhesive to dry for one to two minutes before laying the pad and then walk pad into adhesive at the wall and all seam areas.

CLEANUP

Use soapy water while the adhesive is wet. If dried, use Touchdown #9 Adhesive Remover/Stripper.

RECOMMENDED TOOLS

Application Tools	Coverage
Scrap of pad or carpet	Up to 200 sq. ft. per gallon or approximately 1,000 linear ft. per gallon

* Coverage is approximate and may vary depending on porosity of substrate.

**IT IS THE INSTALLER'S RESPONSIBILITY TO APPLY THE PROPER AMOUNT OF ADHESIVE FOR THE JOB CONDITION.

OTHER PROPERTIES:

Appearance: Beige liquid

Shelf life: One year in unopened container at 70°F.

Other features: Freeze/thaw stable to 10° F [-12.22°C]. Made with anti-microbial agents that will provide its dry film with protection from fungal growth. This protection is determined using the ASTM G21 test method.

CAUTION

DO NOT take internally. If swallowed, DO NOT induce vomiting.

Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.

WARRANTY INFORMATION

This product is manufactured according to exacting quality control standards and is warranted to be free from manufacturing defects. Defective material called to our attention within one year of manufacture will be replaced. No guarantee, expressed or implied, is made regarding the performance of this product since the manner and conditions of application are beyond our control. For complete warranty information, call Technical Services at 800-868-4583 ext 2221, visit us on the web at www.wftaylor.com or e-mail us at tech@wftaylor.com.