

## APPROVED BASE TYPES

• Rubber • Vinyl • Rubber/Vinyl Blends • Carpet •

## DESCRIPTION

Cross the finish line first with Finale®. With its immediate grab, Finale® holds the pressure of inner and outer corners, allowing you to give your job site the final touch. Finale® works flawlessly over multiple surfaces and has good plasticizer migration resistance to firmly hold your bases.

## APPROVED SUBSTRATES & SURFACES

Can be used over most porous wall types including, but not limited to:

- Dry wall (including painted and primed)
- Plywood
- Concrete
- Concrete block

### PRECAUTIONARY NOTE:

- Not recommended for use over waterproof or non-porous panels or coatings

## SUBSTRATE & SURFACE PREPARATION

Follow base manufacturer's guidelines.

- Walls and base must be clean, dry, smooth and structurally sound. They shall be free of any foreign materials that might prevent adhesive bond, including dust, dirt, solvent, loose paint, wax, oil, grease, residual adhesive, adhesive removers, incompatible sealers, fire-retardant chemicals, fungicides, release agents, alkaline salts, excessive carbonation, laitance, mold, mildew, and curing, sealing, hardening or parting compounds.
- Fill all surface cracks, grooves and depressions with appropriate filler based on wall type.
- The substrate, adhesive and base must be acclimated in an enclosed building with the HVAC operational between 60-95°F (15-35°C), and between 30-65% relative humidity, for at least 72 hours before, during and after the installation.

### PRECAUTIONARY NOTE:

- Base must be acclimated per manufacturer's guidelines.

## APPLICATION INSTRUCTIONS

Follow base manufacturer's guidelines for layout, design and any special precautions for installation.


1. Spread adhesive using recommended tools (see tool chart below).
2. Install base immediately after adhesive is spread.
  - Working time is approximately 30 min under acceptable temperature and humidity conditions.
3. Roll base with hand roller to ensure proper transfer of adhesive.

### PRECAUTIONARY NOTE:

- Reseal lid or cap between use to protect product.

## RECOMMENDED TOOLS AND COVERAGE

\*Trowel dimensions are width X depth X spacing. Coverage is approximate and may vary depending on porosity of substrate and the angle at which the tool is held.

Tool* (images not to scale)		Estimated Coverage
3/32" x 3/32" x 3/32" (2.4mm x 2.4mm x 2.4mm) V Notch		4" base: up to 280 lf/gal
When using cartridges, a fan tip is recommended.		

*It is the sole responsibility of the contractor/installer to determine the proper porosity of the subfloor, apply the proper amount of adhesive for the job conditions and ensure that all instructions, procedures and practices are strictly adhered to.*

## CLEANING INSTRUCTIONS

**While product is still wet:** use a damp cloth and water to remove.

**While product is still soft:** use Taylor Touchdown #9 adhesive remover/stripper, denatured alcohol or mineral spirits. Always check compatibility on a piece of scrap flooring.

See next page for Product Characteristics

### PRODUCT CHARACTERISTICS

<b>Base Chemistry</b>	Latex emulsion
<b>Curing Method</b>	Air dry
<b>Appearance</b>	White
<b>Consistency</b>	Smooth, high viscosity mastic
<b>Application</b>	Easy gunning and troweling
<b>Flammability</b>	Non-flammable
<b>Freeze/Thaw</b>	Stable to 10°F (-12°C)
<b>Shelf Life</b>	2 years
<b>Moisture Control</b>	N/A
<b>RH</b>	N/A
<b>pH</b>	N/A
<b>MVER</b>	N/A
<b>Open Time</b>	0 min
<b>Dry Time</b>	N/A
<b>Working Time</b>	30 min
<b>Cure Time</b>	12 hrs
<b>Pot Life</b>	N/A
<b>Light Traffic</b>	N/A
<b>Heavy Traffic</b>	N/A
<b>Heavy Rolling Loads</b>	N/A
<b>Solvents</b>	None
<b>Isocyanates</b>	None
<b>VOC (g/L) - SCAQMD Rule#1168</b>	8
<b>LEED Points</b>	Contributes to low emitting materials
<b>Certifications</b>	Greenguard, FloorScore, CRI Green Label Plus
<b>IIC (Delta)</b>	N/A
<b>STC (Delta)</b>	N/A

### MOISTURE

### TIME

### TRAFFIC

### SUSTAINABILITY

### ACOUSTICS

### STORAGE

This product should be stored at temperatures between 50-90°F (15-32° C). While this product is freeze-thaw stable, it is necessary to protect it from freezing. Freeze/thaw stable to 10°F (-12°C).

### CAUTION

DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.

### WARRANTY INFORMATION

For warranty information, call Technical Services at **(800) 868-4583, Ext: 2221**, visit us on the web at **www.wftaylor.com** or e-mail us at **tech@wftaylor.com**. Flooring manufacturer's and Taylor's written pre-installation and installation instructions must be strictly followed or the Taylor warranty will be void.