**SCS Global Services** does hereby certify that an independent assessment has been conducted on behalf of:

# W.F. Taylor Co., Inc.

800 College Dr., Dalton, CA, United States

For the following product(s):

See Addendum

The product(s) meets all of the necessary qualifications to be certified for the following claim:

## FloorScore®

Indoor Air Quality Certified to SCS-EC10.3-2014 v4.1

Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350), effective April 1, 2017, for the school classroom and private office parameters when modeled as Flooring. Also, conforms to the SCAQMD Rule 1168 - Adhesive and Sealants (October 2017).

Standard Product Application Amount: 680.4 g/m<sup>2</sup>

Measured Concentration of Total Volatile Organic Compounds (TVOC): 0.5 – 5.0 mg/m³ (in compliance with CDPH/EHLB Standard Method v1.2-2017)

Methylene Chloride and Perchloroethylene are not intentionally added to certified products.

Registration # SCS-FS-03175

Valid from: October 1, 2023 to September 30, 2024

SCS Global Services is currently the only certification body approved by the Resilient Floor Covering Institute (RFCI) to provide FloorScore® product certification; certified products are only listed on the SCS Green Products Guide, http://www.scsglobalservices.com/certified-green-products-guide.







Tranky Mather Kam

Stanley Mathuram, PE, Executive Vice President SCS Global Services

2000 Powell Street, Ste. 600, Emeryville, CA 94608 USA

### **Certification Addendum**

## W.F. Taylor Co., Inc.

Certification: Registration # SCS-FS-03175 | Valid from: October 1, 2023 to September 30, 2024

SCS Global Services is currently the only certification body approved by the Resilient Floor Covering Institute (RFCI) to provide FloorScore® product certification; certified products are only listed on the SCS Green Products Guide, http://www.scsglobalservices.com/certified-green-products-guide.

## Addendum Conformance:

## FloorScore<sup>®</sup>

Indoor Air Quality Certified to SCS-EC10.3-2014 v4.1

Conforms to the CDPH/EHLB Standard Method v1.2-2017 (California Section 01350), effective April 1, 2017, for the school classroom and private office parameters when modeled as Flooring. Also, conforms to the SCAQMD Rule 1168 - Adhesive and Sealants (October 2017).

Standard Product Application Amount: 680.4 g/m<sup>2</sup>

Measured Concentration of Total Volatile Organic Compounds (TVOC): 0.5 – 5.0 mg/m³ (in compliance with CDPH/EHLB Standard Method v1.2-2017)

Methylene Chloride and Perchloroethylene are not intentionally added to certified products.

#### **Products: Flooring Adhesives:**

WF Taylor Adhesives 2025, 2027, 2033, 2037, 2040, 2049, 2062, 2071, 2082, 2083, 2084, 2087, 2090, 2091, 2098, Agile, Aspen, Dynamic, Elevate, Enhance, Enviro Poxy 501, Finale, Gravity, IronWood, Ironwood Glue Assist, MS Bond-N-Weld, MS Plus Advance, MS Plus Resilient MBA, Pinnacle, PS 580, Redi-Set, Resolute, RidgeLine, Sahara, SoundLevel, Steadfast, VersaTile, Zephyr

